CLEANINGINSTRUCTIONS



WASHING:

The ideal way to remove dirt, debris and saw chips before washing is with compressed air or air blowers. (Do not spray water into flutes of panels.)

Cleaning from time to time is essential. After blowing out debris, wipe down the outside of panel with a soft rag or sponge and a mild soap/water solution (e.g. Palmolive dish washing detergent).

Do not use scrub brushes as these will scratch panels. Then simply rinse with clear water and dry water droplets with a soft cloth or chamois.

ALWAYS TEST THE SELECTED CLEANING AGENT AND METHOD ON A SMALL UNOBTRUSIVE AREA TO VARIFY THAT THE PANEL SURFACE IS NOT DAMAGED, BEFORE CLEANING THE ENTIRE GLAZING SYSTEM

SUGGESTED DETERGENTS:

- TOP JOB by Proctor & Gamble
- JOY by Proctor & Gamble
- WINDEX by Drackett Products
- PALMOLIVE LIQUID by Colgate Palmolive

Approved detergents are compatible with the Danpalon® sheet products only when the manufacturer's recommendations and instructions are followed.

REMOVAL OF FOREIGN SUBSTANCES

To remove stubborn stains such as grease, adhesives, fresh paint splashes, silicones, inks, etc., the use of VM&P Naphtha, Isopropyl Alcohol, Kerosene, or Petroleum Spirits will generally soften the stain for removal. It is very important to only work a small area (60x60 cm) at any one time. After removal of stains, a final wash and rinse should be made following the suggested washing instructions. The use of duct tape often works well for removal of old paint.

For all mentioned chemicals consult the manufacturer's material safety datasheet (MSDS) for proper safety Precautions

SOME IMPORTANT "DON'TS":

- Never use unapproved cleaners such as highly abrasive polishes, muriatic acid, methyl
 ethyl ketone, alkaline, acetone, gasoline, benzine, aromatic or halogenated solvents,
 etc. They may damage DANPALON sheet products.
- Don't leave cleaners on the sheet for long periods, wash immediately.
- Avoid cleaning DANPALON® in hot sun or at elevated temperatures as this may dry the water droplets rapidly, creating hard water deposit stains.
- Avoid use of cleaning tools on DANPALON products, such as brushes, squeegees, razor blades or scrapers.
- Don't use alcohols on the UV protected surfaces of the DANPALON® sheets.